

CHAPTER 3

Lists, Stacks, and Queues

3.1

```
template <typename Object>
void printLots(list <Object> L, list<int> P)
{
    typename list < int > ::const_iterator pIter ;
    typename list < Object >::const_iterator lIter ;
    int start = 0;
    lIter = L.begin();
    for (pIter=P.begin(); pIter != P.end() && lIter != L.end(); pIter++)
    {
        while (start < *pIter && lIter != L.end())
        {
            start++;
            lIter++;
        }
        if (lIter !=L.end())
        cout<<*lIter<<endl;
    }
}
```

This code runs in time $P.end() - start$, or largest number in P list.

3.2 (a) Here is the code for single linked lists:

```
// beforeP is the cell before the two adjacent cells that are to be
// swapped
// Error checks are omitted for clarity
void swapWithNext(Node * beforep)
{
    Node *p , *afterp;
    p = before->next;
    afterp = p->next; // both p and afterp assumed not NULL
    p->next = afterp-> next;
    beforep ->next = afterp;
    afterp->next = p;
}
```

(b) Here is the code for doubly linked lists:

```
// p and afterp are cells to be switched. Error checks as before
{
    Node *beforep, *afterp;
    beforep = p->prev;
    afterp = p->next;
    p->next = afterp->next;
    beforep->next = afterp;
    afterp->next = p;
    p->next->prev = p;
    p->prev = afterp;
    afterp->prev = beforep;
}
```

3.3

```
template <typename Iterator, typename Object>
Iterator find(Iterator start, Iterator end, const Object& x)
{
    Iterator iter = start;
    while ( iter != end && *iter != x)
```

```

    iter++;
    return iter;
}

```

3.4

```

// Assumes both input lists are sorted
template <typename Object>
list<Object> intersection( const list<Object> & L1,
                           const list<Object> & L2)
{
    list<Object> intersect;
    typename list<Object>:: const_iterator iterL1 = L1.begin();
    typename list<Object>:: const_iterator iterL2= L2.begin();
    while(iterL1 != L1.end() && iterL2 != L2.end())
    {
        if (*iterL1 == *iterL2)
        {
            intersect.push_back(*iterL1);
            iterL1++;
            iterL2++;
        }
        else if (*iterL1 < *iterL2)
            iterL1++;
        else
            iterL2++;
    }
    return intersect;
}

```

3.5

```

// Assumes both input lists are sorted
template <typename Object>
list<Object> listUnion( const list<Object> & L1,
                        const list<Object> & L2)
{
    list<Object> result;
    typename list<Object>:: const_iterator iterL1 = L1.begin();
    typename list<Object>:: const_iterator iterL2= L2.begin();
    while(iterL1 != L1.end() && iterL2 != L2.end())
    {
        if (*iterL1 == *iterL2)
        {
            result.push_back(*iterL1);
            iterL1++;
            iterL2++;
        }
        else if (*iterL1 < *iterL2)
        {
            result.push_back(*iterL1);
            iterL1++;
        }
        else
        {
            result.push_back(*iterL2);
            iterL2++;
        }
    }
    return result;
}

```

3.6 This is a standard programming project. The algorithm can be sped up by setting $M' \equiv M \pmod{N}$, so that the hot potato never goes around the circle more than once. If $M' > N/2$, the potato should be passed in the reverse direction. This requires a doubly linked list. The worst case running time

is clearly $O(N \min(M, N))$, although when the heuristics are used, and M and N are comparable, the algorithm might be significantly faster. If $M = 1$, the algorithm is clearly linear.

```
#include <iostream>
#include <list>
using namespace std;
int main()
{
    int i,j, n, m, mPrime, numLeft;
    list<int> L;
    list<int>::iterator iter;
//Initialization
    cout<<"enter N (# of people) & M (# of passes before elimination):";
    cin>>n>>m;
    numLeft = n;
    mPrime = m % n;
    for (i = 1 ; i <= n; i++)
        L.push_back(i);
    iter = L.begin();
// Pass the potato
    for (i = 0; i < n; i++)
    {
        mPrime = mPrime % numLeft;
        if (mPrime <= numLeft/2) // pass forward
            for (j = 0; j < mPrime; j++)
            {
                iter++;
                if (iter == L.end())
                    iter = L.begin();
            }
        else // pass backward
            for (j = 0; j < mPrime; j++)
            {
                if (iter == L.begin())
                    iter = --L.end();
                else
                    iter--;
            }
        cout<<*iter<< " ";
        iter= L.erase(iter);
        if (iter == L.end())
            iter = L.begin();
    }
    cout<<endl;
    return 0;
}
```

3.7 $O(N^2)$. The trim method reduces the size of the array, requiring each add to resize it. The resize takes $O(N)$

time, and there are $O(N)$ calls.

```
// if out of bounds, writes a message (could throw an exception)
Object & operator[]( int index )
{
    if (index >=0 && index <size() )
        return objects[ index ];
    else
        cout<<"index out of bounds\n";
        return objects[0];
}
const Object & operator[]( int index ) const
{
```

```

    if (index >= 0 && index < size() )
        return objects[ index ];
    else
        cout<<"index out of bounds\n";
        return objects[0];
}

```

3.8

```

iterator insert(iterator pos, const Object& x)
{
    Object * iter = &objects[0];
    Object *oldArray = objects;
    theSize++;
    int i;
    if (theCapacity < theSize)
        theCapacity = theSize;
    objects = new Object[ theCapacity ];
    while(iter != pos)
    {
        objects[i] = oldArray[i];
        iter += sizeOf(Object);
        pos += sizeOf(Object);
        i++;
    }
    objects[pos] = x;
    for (int k = pos+1; k < theSize; k++)
        objects[k] = oldArray[ k ];
    delete [ ] oldArray;
    return & objects[pos];
}

```

3.9 All the aforementioned functions may require the creation of a new array to hold the data. When this occurs all the old pointers (iterators) are invalid.

3.10 The changes are the const_iterator class, the iterator class and changes to all Vector functions that use or return iterators. These classes and functions are shown in the following three

(a)

```

class const_iterator
{
public:
//const_iterator( ) : current( NULL )
// { } Force use of the safe constructor
    const Object & operator* ( ) const
    { return retrieve( ); }
    const_iterator & operator++ ( )
    {
        current++;
        return *this;
    }
    const_iterator operator++ ( int )
    {
        const_iterator old = *this;
        ++( *this );
        return old;
    }

    bool operator== ( const const_iterator & rhs ) const
    { return current == rhs.current; }
    bool operator!= ( const const_iterator & rhs ) const
    { return !( *this == rhs ); }
}

```

```

protected:
    Object *current;
    const Vector<Object> *theVect;
    Object & retrieve( ) const
    {
        assertIsValid();
        return *current;
    }
    const_iterator( const Vector<Object> & vect, Object *p ) :theVect (& vect), current( p ) { }
    void assertIsValid() const
    {
        if (theVect == NULL || current == NULL )
            throw IteratorOutOfBoundsException();
    }
    friend class Vector<Object>;
};


```

(b)

```

class iterator : public const_iterator
{
public:
    //iterator( )
    // { } Force use of the safe constructor
    Object & operator* ( ) { return retrieve( ); }
    const Object & operator* ( ) const { return const_iterator::operator*( ); }
    iterator & operator++ ( )
    {
        cout<<"old "<<*current<<" ";
        current++;
        cout<<" new "<<*current<<" ";
        return *this;
    }

    iterator operator++ ( int )
    {
        iterator old = *this;
        ++( *this );
        return old;
    }
protected:
    iterator(const Vector<Object> & vect, Object *p ) : const_iterator(vect, p ) { }
    friend class Vector<Object>;
};


```

(c)

```

iterator begin( )
    { return iterator(*this ,&objects[ 0 ]); }
const_iterator begin( ) const
    { return const_iterator(*this,&objects[ 0 ]); }
iterator end( )
    { return iterator(*this, &objects[ size( ) ]); }
const_iterator end( ) const
    { return const_iterator(*this, &objects[ size( ) ]); }


```

3.11

```

template <typename Object>
struct Node
{
    Object data;
    Node * next;
    Node ( const Object & d = Object(), Node *n = NULL ) : data(d) , next(n) {}
};


```

```

template <typename Object>
class singleList
{
public:
    singleList( ) { init(); }
    ~singleList() { eraseList(head); }
    singleList( const singleList & rhs)
    {
        eraseList(head);
        init();
        *this = rhs;
    }

    bool add(Object x)
    {
        if (contains(x))
            return false;
        else
        {
            Node<Object> *ptr = new Node<Object>(x);
            ptr->next = head->next;
            head->next = ptr;
            theSize++;
        }
        return true;
    }

    bool remove(Object x)
    {
        if (!contains(x))
            return false;
        else
        {
            Node<Object>*ptr = head->next;
            Node<Object>*trailer;
            while(ptr->data != x)
                { trailer = ptr;
                  ptr=ptr->next;
                }
            trailer->next = ptr->next;
            delete ptr;
            theSize--;
        }
        return true;
    }

    int size() { return theSize; }

    void print()
    {
        Node<Object> *ptr = head->next;
        while (ptr != NULL)
        {
            cout<< ptr->data<< " ";
            ptr = ptr->next;
        }
        cout<<endl;
    }

    bool contains(const Object & x)
    {
        Node<Object> * ptr = head->next;
        while (ptr != NULL)
        {

```

```

        if (x == ptr->data)
            return true;
        else
            ptr = ptr->next;
    }
    return false;
}

void init()
{
    theSize = 0;
    head = new Node<Object>;
    head->next = NULL;
}

void eraseList(Node<Object> * h)
{
    Node<Object> *ptr= h;
    Node<Object> *nextPtr;
    while(ptr != NULL)
    {
        nextPtr = ptr->next;
        delete ptr;
        ptr= nextPtr;
    }
};

private:
    Node<Object> *head;
    int theSize;
};

```

3.12

```

template <typename Object>
struct Node
{
    Object data;
    Node * next;
    Node ( const Object & d = Object(), Node *n = NULL ) : data(d) , next(n) {}

template <typename Object>
class singleList
{
public:
    singleList( ) { init(); }
    ~singleList(){ eraseList(head);}
    singleList( const singleList & rhs)
    {
        eraseList(head);
        init();
        *this = rhs;
    }

    bool add(Object x)
    {
        if (contains(x))
            return false;
        else
        {
            Node<Object> *ptr = head->next;
            Node<Object>* trailer = head;
            while(ptr && ptr->data < x)
            {

```

```

        trailer = ptr;
        ptr = ptr->next;
    }
    trailer->next = new Node<Object> (x);
    trailer->next->next = ptr;
    theSize++;
}
return true;
}

bool remove(Object x)
{
    if (!contains(x))
        return false;
    else
    {
        Node<Object>*ptr = head->next;
        Node<Object>*trailer;
        while(ptr->data != x)
        {
            trailer = ptr;
            ptr=ptr->next;
        }
        trailer->next = ptr->next;
        delete ptr;
        theSize--;
    }
    return true;
}

int size() { return theSize; }

void print()
{
    Node<Object> *ptr = head->next;
    while (ptr != NULL)
    {
        cout<< ptr->data<<" ";
        ptr = ptr->next;
    }
    cout<<endl;
}

bool contains(const Object & x)
{
    Node<Object> * ptr = head->next;
    while (ptr != NULL && ptr->data <= x )
    {
        if (x == ptr->data)
            return true;
        else
            ptr = ptr-> next;
    }
    return false;
}

void init()
{
    theSize = 0;
    head = new Node<Object>;
    head-> next = NULL;
}

```

```

void eraseList(Node<Object> * h)
{
    Node<Object> *ptr= h;
    Node<Object> *nextPtr;
    while(ptr != NULL)
    {
        nextPtr = ptr->next;
        delete ptr;
        ptr= nextPtr;
    }
};

private:
    Node<Object> *head;
    int theSize;
};

```

3.13 Add the following code to the const_iterator class. Add the same code with iterator replacing const_iterator to the iterator class.

```

const_iterator & operator-- ( )
{
    current = current->prev;
    return *this;
}
const_iterator operator-- ( int )
{
    const_iterator old = *this;
    --( *this );
    return old;
}

```

3.14

```

const_iterator & operator+ ( int k )
{
    const_iterator advanced = *this;
    for (int i = 0; i < k ; i++)
        advanced.current = advanced.current->next;
    return advanced;
}

```

3.15

```

void splice (iterator itr, List<Object> & lst)
{
    itr.assertIsValid();
    if (itr.theList != this)
        throw IteratorMismatchException ();
    Node *p = iter.current;
    theSize += lst.size();
    p->prev->next = lst.head->next;
    lst.head->next->prev = p->prev;
    lst.tail->prev->next = p;
    p->prev = lst->tail->prev;
    lst.init();
}

```

3.16

The class const_reverse_iterator is almost identical to const_iterator while reverse_iterator is almost identical to iterator. Redefine `++` to be `-` and vice versa for both the pre and post operators for both classes as well as changing all variables of type const_iterator to const_reverse_iterator and changing iterator to reverse_iterator. Add two new members in list for `rbegin()` and `rend()`.

```

// In List add
const_reverse_iterator rbegin() const
{
    return const_reverse_iterator itr( tail);
}

const_reverse_iterator rend() const
{
    const_reverse_iterator itr(head);
}

reverse_iterator rbegin()
{
    return reverse_iterator itr( tail);
}

reverse_iterator rend()
{
    reverse_iterator itr(head);
}

```

3.17 changed functions listed below

For the `class const_iterator`

```

const_iterator( ) : current( nullptr )
{ }

const Object & operator* ( ) const
{
    assertIsValid();
    return retrieve( );
}

const_iterator & operator++ ( )
{
    assertIsValid();
    current = current->next;
    return *this;
}

const_iterator operator++ ( int )
{
assertIsValid();
const_iterator old = *this;
+( *this );
return old;
}

protected:
Node *current;
const List<Object> *theList;
const_iterator(const List<Object> &lst, Node *p) : theList(&lst),current(p)
{}

void assertIsValid() const
{
    if (theList == nullptr || current == nullptr || current == theList->head)
        throw IteratorOutOfBoundsException();
}

```

}

For the class `class iterator : public const_iterator`

```
Object & operator* ( )
{
    assertIsValid();

    return const_iterator::retrieve( );
}
const Object & operator* ( ) const
{
    assertIsValid();
    return const_iterator::operator*( );
}

iterator & operator++ ( )
{
    assertIsValid();
    this->current = this->current->next;
    return *this;
}

iterator operator++ ( int )
{
    assertIsValid();
    iterator old = *this;
    +( *this );
    return old;
}

protected:
iterator(const List<Object> & lst, Node *p ): const_iterator(lst,p)
{ }
```

For the List class

```
iterator begin( )
{
    iterator itr(*this, head);
    return ( ++itr );
}
const_iterator begin( ) const
{
    const_iterator itr(*this, head);
    return ( ++itr );
}
iterator end( )
{
    iterator itr(*this, tail);
    return ( itr );
}
const_iterator end( ) const
{
    iterator itr(*this, tail);
    return ( itr );
}

iterator insert( iterator itr, const Object & x )
{
    itr.assertIsValid();
```

```

    if (itr.theList != this)
        throw IteratorMismatchException();

    Node *p = itr.current;
    theSize++;
    return (*this, p->prev = p->prev->next = new Node( x, p->prev, p ) );
}

iterator insert( iterator itr, Object && x )
{
    itr.assertIsValid();
    if (iter.theList != this)
        throw IteratorMismatchException();

    Node *p = itr.current;
    theSize++;
    return { p->prev = p->prev->next
              = new Node{ std::move( x ), p->prev, p } };
}

iterator erase( iterator itr )
{
    Node *p = itr.current;

    itr.assertIsValid();
    if (itr.theList != this)
        throw IteratorMismatchException();
    iterator retVal(*this, p->next );
    p->prev->next = p->next;
    p->next->prev = p->prev;
    delete p;
    theSize--;

    return retVal;
}

iterator erase( iterator from, iterator to )
{
    for( iterator itr = from; itr != to; )
    {
        itr.assertIsValid();
        if (iter.theList != this)
            throw IteratorMismatchException();

        itr = erase( itr );
    }
    return to;
}

```

3.18 Add a boolean data member to the node class that is true if the node is active; and false if it is “stale.” The erase method changes this data member to false; iterator methods verify that the node is not stale.

3.19 Without head or tail nodes the operations of inserting and deleting from the end becomes a $O(N)$ operation where the N is the number of elements in the list. The algorithm must walk down the list before inserting at the end. With the head node insert needs a special case to account for when

something is inserted before the first node.

3.20 (a) The advantages are that it is simpler to code, and there is a possible saving if deleted keys are subsequently reinserted (in the same place). The disadvantage is that it uses more space, because each cell needs an extra bit (which is typically a byte), and unused cells are not freed.

(b) Add a int numDeleted to the list (initialized to 0) and a bool deleted to Node (initialized to false)

```
void garbageCollection()
{
    Node *p = head->next;
    Node *q;
    while (p!= tail)
    {
        if (p->deleted == true)
        {
            q = p->prev;
            p->prev->next = p->next;
            p->next->prev = p->prev;
            delete p;
            p = q;
        }
        p = p->next;
    }
    numDeleted = 0;
}

iterator erase( iterator itr )
{
    Node *p = itr.current;
    Node *q; p->deleted = true;
    numDeleted++;
    theSize--;
    if (numDeleted >= theSize)
        garbageCollection();
    iterator retVal(*this, p->next );
    return retVal;
}
```

3.21 (b)

```
/*
 Weiss Exercise 3_21 Balanced parenthesis for c++
 */
#include <iostream>
#include <stack>
#include <string>
#include <fstream>
using namespace std;

int main()
{
    string fileName;
    stack<char> match;
    bool balanced = true;
```

```

string line;
ifstream in;
int i;
int lineNumber = 0;
char x;

cout<<"what is the name of the file: ";
cin>>fileName;
in.open(fileName.c_str());

getline(in, line);
while (in && balanced)
{
    lineNumber++;
    for ( i= 0; i< line.size(); i++)
    {
        x = line[i];
        if (x == '\"') // skip chars in double quotes
        {
            i++;
            while (x != '\"')
                x++;
        }
        else if (x == '\'') // skip chars in single quotes
        {
            i++;
            while (x != '\'')
                x++;
        }
        else if (x == '\\\'' && i < line.size()-1 && line[i+1] == '\\\'')
            getline(in, line);
        else if (x == '(' || x == '[' || x == '{')
            match.push(x);
        else if (x == ')')
        {
            if (match.top()!='(') balanced = false;
            match.pop();
        }
        else if (x == ']')
        {
            if (match.top()!='[') balanced = false;
            match.pop();
        }
        else if (x == '}')
        {
            if (match.top()!='{') balanced = false;
            match.pop();
        }
        else if (x == '/' && i < line.size() -1 && line[++i] == '*')
            match.push('/');
        else if (x== '*' && i < line.size() -1 && line[++i] == '/')
        {
            if (match.top()!='/') balanced = false;
            match.pop();
        }
    }
    getline(in, line);
}

```

```

if (balanced)
    cout<<"the symbols balanced \n";
else
    cout<<"mismatched symbol on line "<<lineNumber<<endl;
}

```

3.22 The following function evaluates a postfix expression, using $+$, $-$, $*$, $/$ and $^$ ending in $=$. It requires spaces between all operators and $=$ and uses the stack, string and math.h libraries. It only recognizes 0 in input as 0.0.

```

double evalPostFix( )
{
    stack<double> s;
    string token;
    double a, b, result;
    cin>> token;
    while (token[0] != '=')
    {
        result = atof (token.c_str());
        if (result != 0.0 )
            s.push(result);
        else if (token == "0.0")
            s.push(result);
        else
            switch (token[0])
            {
                case '+': a = s.top(); s.pop(); b = s.top();
                            s.pop(); s.push(a+b); break;
                case '-': a = s.top(); s.pop(); b = s.top();
                            s.pop(); s.push(a-b); break;
                case '*': a = s.top(); s.pop(); b = s.top();
                            s.pop(); s.push(a*b); break;
                case '/': a = s.top(); s.pop(); b = s.top();
                            s.pop(); s.push(a/b); break;
                case '^': a = s.top(); s.pop(); b = s.top();
                            s.pop(); s.push(exp(a*log(b))); break;
            }
            cin>> token;
    }
    return s.top();
}

```

3.23 (a, b) This function will read in from standard input an infix expression of single lower case characters and the operators, $+$, $-$, $/$, $*$, $^$ and $($, $)$, and output a postfix expression.

```

void inToPostfix()
{
    stack<char> s;
    char token;
    cin>> token;
    while (token != '=')
    {
        if (token >= 'a' && token <= 'z')
            cout<<token<<" ";
        else
            switch (token)
            {
                case ')': while(!s.empty() && s.top() != '(')
                            { cout<<s.top()<<" "; s.pop();}
                            s.pop(); break;
                case '(': s.push(token); break;
            }
    }
}

```

```

        case '^' : while(!s.empty() && !(s.top()== '^' || s.top() == '('))
                    {cout<<s.top(); s.pop();}
                    s.push(token); break;
        case '*' :
        case '/' : while(!s.empty() && s.top() != '+' && s.top() != '-' && s.top() != '(')
                    {cout<<s.top(); s.pop();}
                    s.push(token); break;
        case '+' :
        case '-' : while(!s.empty() && s.top() != '(')
                    {cout<<s.top()<<" "; s.pop();}
                    s.push(token); break;
    }
    cin>> token;
}
while (!s.empty())
    {cout<<s.top()<<" "; s.pop();}
cout<<`=\n`;
}

```

(c) The function converts postfix to infix with the same restrictions as above.

```

string postToInfix()
{
    stack<string> s;
    string token;
    string a, b;
    cin>>token;
    while (token[0] != '=')
    {
        if (token[0] >= 'a' && token[0] <= 'z')
            s.push(token);
        else
            switch (token[0])
            {
                case '+' : a = s.top(); s.pop(); b = s.top(); s.pop();
                            s.push("(" + a+ " + " + b+ ")"); break;
                case '-' : a = s.top(); s.pop(); b = s.top(); s.pop();
                            s.push("(" + a+ " - " + b+ ")"); break;
                case '*' : a = s.top(); s.pop(); b = s.top(); s.pop();
                            s.push("(" + a+ " * " + b+ ")"); break;
                case '/' : a = s.top(); s.pop(); b = s.top(); s.pop();
                            s.push("(" + a+ " / " + b+ ")"); break;
                case '^' : a = s.top(); s.pop(); b = s.top(); s.pop();
                            s.push("(" + a+ " ^ " + b+ ")"); break;
            }
        cin>> token;
    }
    return s.top();
} //Converts postfix to infix

```

3.24 Two stacks can be implemented in an array by having one grow from the low end of the array up, and the other from the high end down.

3.25 (a) Let E be our extended stack. We will implement E with two stacks. One stack, which we'll call S , is used to keep track of the $push$ and pop operations, and the other M , keeps track of the minimum. To implement $E.push(x)$, we perform $S.push(x)$. If x is smaller than or equal to the top element in stack M , then we also perform $M.push(x)$. To implement $E.pop()$ we perform $S.pop()$. If x is equal to the top element in stack M , then we also $M.pop()$. $E.findMin()$ is performed by examining the top of M . All these operations are clearly $O(1)$.

(b) This result follows from a theorem in Chapter 7 that shows that sorting must take $\Omega(N \log N)$ time. $O(N)$ operations in the repertoire, including $deleteMin$, would be sufficient to sort.

3.26 Three stacks can be implemented by having one grow from the bottom up, another from the top down and a third somewhere in the middle growing in some (arbitrary) direction. If the third stack collides with either of the other two, it needs to be moved. A reasonable strategy is to move it so that its center (at the time of the move) is halfway between the tops of the other two stacks.

3.27 Stack space will not run out because only 49 calls will be stacked. However the running time is exponential, as shown in Chapter 2, and thus the routine will not terminate in a reasonable amount of time.

3.28 This requires a doubly linked list with pointers to the head and the tail In fact it can be implemented with a list by just renaming the list operations.

```
template <typename Object>
class deque
{
public:
    deque() { l(); }
    void push (Object obj) { l.push_front(obj); }
    Object pop () { Object obj=l.front(); l.pop_front(); return obj; }
    void inject(Object obj); { l.push_back(obj); }
    Object eject(); { pop_back(obj); }
private:
    list<Object> l;
}; //
```

3.29 Reversal of a singly linked list can be done recursively using a stack, but this requires $O(N)$ extra space. The following solution is similar to strategies employed in garbage collection algorithms (*first* represents the first node in the non-empty node in the non-empty list). At the top of the *while* loop the list from the start to *previousPos* is already reversed, whereas the rest of the list, from *currentPos* to the end is normal. This algorithm uses only constant extra space.

```
//Assuming no header and that first is not NULL
Node * reverseList(Node *first)
{
    Node * currentPos, *nextPos, *previousPos;
    previousPos = NULL;
    currentPos = first;
    nextPos = first->next;
    while (nextPos != NULL)
    {
        currentPos -> next = previousPos;
        previousPos = currentPos;
        currentPos = nextPos;
        nextPos = nextPos -> next;
    }
    currentPos->next = previousPos;
    return currentPos;
}
```

3.30 (c) This follows well-known statistical theorems. See Sleator and Tarjan's paper in Chapter 11 for references.

3.31

```
template <typename Object>
struct node
{
    node () { next = NULL; }
    node (Object obj) : data(obj) {}
    node (Object obj, node * ptr) : data(obj), next(ptr) {}
    Object data;
    node * next;
};

template <typename Object>
class stack
{
public:
    stack () { head = NULL; }
    ~stack() { while (head) pop(); }
}

void push(Object obj)
{
    node<Object> * ptr = new node<Object>(obj, head);
    head= ptr;
}

Object top()
{return (head->data);}

void pop()
{
    node<Object> * ptr = head->next;
    delete head;
    head = ptr;
}

private:
node<Object> * head;
};
```

3.32

```
template <typename Object>
class queue
{
public:
    queue () { front = NULL; rear = NULL; }
    ~queue() { while (front) deque(); }

    void enqueue(Object obj)
    {
        node<Object> * ptr = new node<Object>(obj, NULL);
        if (rear)
            rear= rear->next = ptr;
        else
            front = rear = ptr;
    }

    Object dequeue()
    {
        Object temp = front->data;
        node<Object> * ptr = front;
        if (front->next == NULL) // only 1 node
            front = rear = NULL;
        else
```

```

        front = front->next;
        delete ptr;
        return temp;
    }

private:
    node<Object> * front;
    node<Object> * rear;
}; //

```

3.33 This implementation holds $\text{maxSize} - 1$ elements.

```

template <typename Object>
class queue
{
public:
queue(int s): maxSize(s), front(0), rear(0) {elements.resize(maxSize);}
queue () { maxSize = 100; front = 0;
rear = 0;elements.resize(maxSize);}
~queue() { while (front!=rear) deque(); }
void enqueue(Object obj)
{
    if (! full())
    {
        elements[rear] = obj;
        rear = (rear + 1) % maxSize;
    }
}
Object deque()
{
Object temp;
if (!empty())
{
    temp= elements[front];
    front = (front +1 ) % maxSize;
    return temp;
}
}
bool empty() {return front == rear;}
bool full() { return (rear + 1) % maxSize == front;}
private:
    int front, rear;
    int maxSize;
    vector<Object> elements ;
}; //

```

3.34 (b) Use two iterators p and q , both initially at the start of the list. Advance p one step at a time, and q two steps at a time. If q reaches the end there is no cycle; otherwise, p and q will eventually catch up to each other in the middle of the cycle.

3.35 (a) Does not work in constant time for insertions at the end

(b) Because of the circularity, we can access the front item in constant time, so this works.

3.36 Copy the value of the item in the next node (that is, the node that follows the referenced node) into the current node (that is, the node being referenced). Then do a deletion of the next node.

3.37 (a) Add a copy of the node in position p after position p ; then change the value stored in position

p to *x*.

(b) Set *p*->*data* = *p*->*next*->*data* and set *p*->*next* = *p*->*next*->*next*. Then delete *p*->*next*. Note that the tail node guarantees that there is always a next node.